




# SHEET METAL UTILITY VENTS


Whether the need for venting at the plate line or the sill line our full range of sheet metal utility vents can do the job. All steel construction assures lasting performance and durability.

## CONTINUOUS VENT




3.53 SQ. IN./LF NFVA  
10<sup>ft</sup> Lengths

## EAVE VENT



PG on  
3 Sides


14" X 3" = 33 SQ. IN. NFVA  
22" X 3" = 52 SQ. IN. NFVA  
22" X 3.5" = 61 SQ. IN. NFVA  
22" X 5.5" = 96 SQ. IN. NFVA



## FOUNDATION ACCESS CRAWL SET

24" X 18" = 220 SQ. IN. NFVA


## FOUNDATION VENT



PG on  
4 Sides


14" X 6" = 71 SQ. IN. NFVA  
14" X 8" = 95 SQ. IN. NFVA

## RAFTER VENT



PG on  
3 Sides

14" X 3" = 33 SQ. IN. NFVA  
22" X 3" = 52 SQ. IN. NFVA  
22" X 3.5" = 61 SQ. IN. NFVA  
22" X 5.5" = 96 SQ. IN. NFVA



## SOFFIT VENT

PG on  
4 Sides

22" X 3.5" = 61 SQ. IN. NFVA  
22" X 5.5" = 96 SQ. IN. NFVA

### MATERIALS

ASTM A653/A653M -G90 hot dipped galvanized steel,28GA.  
ASTM A653/A653M -G90 hot dipped galvanized steel,28GA,  
ASTM D-2092-95 mill phosphatized


### INSTALLATION

Installation shall be in accordance with recognized sheet metal practices per SMACNA Architectural Sheet Metal Manual 5th Edition and NRCA National Roofing and Waterproofing Manual 4th Edition.

Before installing, ensure that the substrate is uniform and even. Do not install C & J Sheet Metal Ventilating Products on an uneven surface.

**NOTE:** Recommended use of this product is for exhaust of warm dry or slightly moist air only. Do not use this product to vent or exhaust grease or liquid.

## STAMPED VENT



Available with  
or without wire mesh

14" X 6" = 25 SQ. IN. NFVA  
14" X 6" WW = 19 SQ. IN. NFVA